



SS-30C

**COLOR MINI VIDEO
AND LIGHTING SYSTEM**

**ONLY 3.0 CM (1.18 INCH IN
DIAMETER)**

EXTREMELY DURABLE

**CRISP, WIDE-ANGLE
IMAGE**

RATED TO 400 METERS



The SS-30C is DeepSea's smallest color video camera with integrated LED lighting, and the replacement to the popular SS-126C. This new and improved version features enhanced resolution, sensitivity and durability. The SS-30C housing is constructed from stainless steel for maximum durability and will not wear in contact with tough materials such as cast iron. Six ultra-bright LED's are built into the camera and protected by a smooth, chip and crack resistant sapphire window. LED lighting provides powerful and virtually indestructible illumination over thousands of hours of use. Each SS-30C is factory pressure-tested and guaranteed to 400 meters underwater.

The SS-30C is designed to withstand the rigors of day-to-day inspection in confined areas where environmental and mechanical shock are unavoidable. The camera has applications in pipe and borehole inspection, fixed-mount monitoring, tank and void inspection, in fisheries and aquaculture, or just about any confined space with access over 1.18 inches. It is also ideal for inspection of machinery and engineering spaces both on land and aboard ship. The SS-30C can be used alone as a drop system, affixed to tools or remote manipulators, and other equipment.

SS-30C Specifications

MECHANICAL

Housing:	Stainless Steel
Window Material:	Sapphire
Outer Diameter:	3.00 cm (1.18 in.)
Overall Length:	4.27 cm (1.68 in.)
Weight in Air:	96.39 g (3.4 oz)

VIDEO

Image Sensor:	1/3" Interline Transfer CCD
Min. Depth of Field:	1/2 -inch
Focus:	Fixed focus, factory set
Resolution:	460 (H) x 350 (V)
Number of Pixels:	768 (H) x 494 (V)
Scene Illumination:	0.5 Lux
Lens:	2 mm, f3.5 wide-angle
Shutter:	Electronic, automatic
Angle of View in Air:	83 (H) x 60 (V) 95 (D)
Angle of View in Water:	59 (H) x 44 (V) 68 (D)
Video Output:	1.0 volt peak-to-peak at 75 ohm
Video Format:	Color, NTSC or PAL
Lighting:	6 Luxeon white LED's


ENVIRONMENTAL

Depth:	400 meters (1312 feet)
Operating Temperature:	-10° C to 50° C (14° F to 122° F)
Storage Temperature:	-10° C to 60° C (14° F to 140° F)

ELECTRICAL

Power Requirement:	8 to 13 volts DC
Current:	160mA (camera), ~500mA with LEDs

Pin-out:



BHSS3MP
1 = Ground
2 = Power
3 = Video



Specifications subject to change without notice

DEEPSEA POWER & LIGHT • 4033 Ruffin Rd. • San Diego, CA 92123 USA • TEL (858) 576-1261 • FAX (858) 576-0219

Web: <http://www.deepsea.com> • e-mail: info@deepsea.com

Rev. 5/14/04